


BT2B 328283/HA1

NR double row tapered roller bearings are ready-to-mount units, manufactured with a predetermined axial clearance or preload. TDI design bearings have a double row inner ring and two outer rings that usually have an intermediate ring between them. Their roller sets are arranged face-to-face (X-arrangement). Design variants include features such as a helical groove in the bore, locating slots in the inner ring, or seals on both sides.



- High radial load carrying capacity
- Accommodate axial loads in both directions
- Relatively high stiffness
- Many variants, including shields, seals, a helical groove in the bore, or locating slots
- Ready to mount

Design variant/feature	TDIT/Y2
Bore type	Cylindrical



Dimensions		
D	590.55 mm	Outside diameter
T	209.55 mm	Total width
B	209.55 mm	Width of inner ring
d ₁	454.8 mm	Shoulder diameter of inner ring (small side face)
D ₁	522.617 mm	Raceway diameter of outer ring (small side face)
r _{3,4}	min. 6.4 mm	Chamfer dimension of outer ring

Calculation data

Basic dynamic load rating	C	4 175 kN
Basic static load rating	C ₀	9 650 kN

Fatigue load limit	P_u	720 kN
Limiting value	e	0.33
Calculation factor	Y_1	2
Calculation factor	Y_2	3
Calculation factor	Y_0	2
Comparative radial load rating	C_F	1 040 kN
Comparative axial load rating	C_{Fa}	332 kN
Thrust factor	K	1.76

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances:
bearings: Normal and CL7C, P5
inch bearings: Normal and CL
- Internal clearance

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit