

32244/DFC460

Matched tapered roller bearings arranged face-to-face (X-arrangement, load lines diverge towards the bearing axis) accommodate high radial loads and axial loads in both directions. The precision manufactured intermediate ring between the outer rings enables a defined internal clearance or preload to be achieved when mounted. Matched tapered roller bearings are typically used in gearboxes, hoisting equipment, rolling mills, and machines in the mining industry.



- High radial load carrying capacity
- Designed for axial loads in both directions
- Relatively high stiffness
- Surface finish on the contact surfaces of the rollers and raceways that enhances operational reliability



Dimensions		
d	220 mm	Bore diameter
D	400 mm	Outside diameter
T	228 mm	Total width
2B	216 mm	Width of inner rings
b	25 mm	Width of lubrication groove
K	18 mm	Diameter of lubrication hole
r _{3,4}	min. 4 mm	Chamfer dimension
r ₅	min. 1.5 mm	Chamfer dimension



Abutment dimensions		
d _a	max. 253 mm	Diameter of shaft abutment
D _a	min. 334 mm	Diameter of housing abutment
D _a	max. 382.5 mm	Diameter of housing abutment
C _a	min. 13 mm	Minimum width of space required in housing on large side face

r_a	max. 5 mm	Radius of fillet
r_c	max. 1.5 mm	Radius of fillet

Calculation data

Basic dynamic load rating	C	2 949 kN
Basic static load rating	C_0	5 400 kN
Fatigue load limit	P_u	465 kN
Reference speed		900 r/min
Limiting speed		1 500 r/min
Limiting value	e	0.43
Calculation factor	Y_1	1.6
Calculation factor	Y_2	2.3
Calculation factor	Y_0	1.6

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal + CL7C, P5, total width
- Internal clearance: values

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit