

32030 X/DFC300

Matched tapered roller bearings arranged face-to-face (X-arrangement, load lines diverge towards the bearing axis) accommodate high radial loads and axial loads in both directions. The precision manufactured intermediate ring between the outer rings enables a defined internal clearance or preload to be achieved when mounted. Matched tapered roller bearings are typically used in gearboxes, hoisting equipment, rolling mills, and machines in the mining industry.



- High radial load carrying capacity
- Designed for axial loads in both directions
- Relatively high stiffness
- Surface finish on the contact surfaces of the rollers and raceways that enhances operational reliability



Dimensions		
d	150 mm	Bore diameter
D	225 mm	Outside diameter
T	96 mm	Total width
2B	96 mm	Width of inner rings
b	10 mm	Width of lubrication groove
K	7.5 mm	Diameter of lubrication hole
r _{3,4}	min. 2.5 mm	Chamfer dimension
r ₅	min. 1 mm	Chamfer dimension



Abutment dimensions		
d _a	max. 165 mm	Diameter of shaft abutment
D _a	min. 200 mm	Diameter of housing abutment
D _a	max. 212.5 mm	Diameter of housing abutment
C _a	min. 8 mm	Minimum width of space required in housing on large side face

r_a	max. 3 mm	Radius of fillet
r_c	max. 1 mm	Radius of fillet

Calculation data

AGA performance class		AGA Explorer
Basic dynamic load rating	C	782 kN
Basic static load rating	C_0	1 320 kN
Fatigue load limit	P_u	132 kN
Reference speed		1 800 r/min
Limiting speed		2 600 r/min
Limiting value	e	0.46
Calculation factor	Y_1	1.5
Calculation factor	Y_2	2.2
Calculation factor	Y_0	1.4

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal + CL7C, P5, total width
- Internal clearance: values

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit