

32028 X/DF

Matched tapered roller bearings arranged face-to-face (X-arrangement, load lines diverge towards the bearing axis) accommodate high radial loads and axial loads in both directions. The precision manufactured intermediate ring between the outer rings enables a defined internal clearance or preload to be achieved when mounted. Matched tapered roller bearings are typically used in gearboxes, hoisting equipment, rolling mills, and machines in the mining industry.



- High radial load carrying capacity
- Designed for axial loads in both directions
- Relatively high stiffness
- Surface finish on the contact surfaces of the rollers and raceways that enhances operational reliability



| Dimensions       |             |                              |
|------------------|-------------|------------------------------|
| d                | 140 mm      | Bore diameter                |
| D                | 210 mm      | Outside diameter             |
| T                | 90 mm       | Total width                  |
| 2B               | 90 mm       | Width of inner rings         |
| b                | 13 mm       | Width of lubrication groove  |
| K                | 7.5 mm      | Diameter of lubrication hole |
| r <sub>3,4</sub> | min. 2 mm   | Chamfer dimension            |
| r <sub>5</sub>   | min. 0.6 mm | Chamfer dimension            |



| Abutment dimensions |             |                                                               |
|---------------------|-------------|---------------------------------------------------------------|
| da                  | max. 153 mm | Diameter of shaft abutment                                    |
| Da                  | min. 187 mm | Diameter of housing abutment                                  |
| Da                  | max. 199 mm | Diameter of housing abutment                                  |
| Ca                  | min. 8 mm   | Minimum width of space required in housing on large side face |

|       |             |                  |
|-------|-------------|------------------|
| $r_a$ | max. 2.5 mm | Radius of fillet |
| $r_c$ | max. 0.6 mm | Radius of fillet |

## Calculation data

|                           |       |              |
|---------------------------|-------|--------------|
| AGA performance class     |       | AGA Explorer |
| Basic dynamic load rating | C     | 692 kN       |
| Basic static load rating  | $C_0$ | 1 160 kN     |
| Fatigue load limit        | $P_u$ | 116 kN       |
| Reference speed           |       | 1 900 r/min  |
| Limiting speed            |       | 2 800 r/min  |
| Limiting value            | e     | 0.46         |
| Calculation factor        | $Y_1$ | 1.5          |
| Calculation factor        | $Y_2$ | 2.2          |
| Calculation factor        | $Y_0$ | 1.4          |

## Tolerances and clearances

### GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal + CL7C, P5, total width
- Internal clearance: values

### BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit