

33015/DFC240

Matched tapered roller bearings arranged face-to-face (X-arrangement, load lines diverge towards the bearing axis) accommodate high radial loads and axial loads in both directions. The precision manufactured intermediate ring between the outer rings enables a defined internal clearance or preload to be achieved when mounted. Matched tapered roller bearings are typically used in gearboxes, hoisting equipment, rolling mills, and machines in the mining industry.



- High radial load carrying capacity
- Designed for axial loads in both directions
- Relatively high stiffness
- Surface finish on the contact surfaces of the rollers and raceways that enhances operational reliability



Dimensions		
d	75 mm	Bore diameter
D	115 mm	Outside diameter
T	62 mm	Total width
2B	62 mm	Width of inner rings
b	7.2 mm	Width of lubrication groove
K	5 mm	Diameter of lubrication hole
r _{3,4}	min. 1.5 mm	Chamfer dimension
r ₅	min. 0.6 mm	Chamfer dimension



Abutment dimensions		
d _a	max. 84 mm	Diameter of shaft abutment
D _a	min. 104 mm	Diameter of housing abutment
D _a	max. 106.5 mm	Diameter of housing abutment
C _a	min. 6 mm	Minimum width of space required in housing on large side face

r_a	max. 1.5 mm	Radius of fillet
r_c	max. 0.6 mm	Radius of fillet

Calculation data

AGA performance class		AGA Explorer
Basic dynamic load rating	C	286 kN
Basic static load rating	C_0	455 kN
Fatigue load limit	P_u	52 kN
Reference speed		3 600 r/min
Limiting speed		5 300 r/min
Limiting value	e	0.3
Calculation factor	Y_1	2.3
Calculation factor	Y_2	3.4
Calculation factor	Y_0	2.2

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal + CL7C, P5, total width
- Internal clearance: values

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit