

BT1B 328017/HA4



Single row tapered roller bearings are designed to accommodate combined radial and axial loads and provide low friction during operation. The inner ring, with rollers and cage, can be mounted separately from the outer ring. These separable and interchangeable components facilitate mounting, dismounting and maintenance. By mounting one single row tapered roller bearing against another and applying a preload, a rigid bearing application can be achieved.

- High radial and axial load carrying capacity
- Accommodate axial loads in one direction
- Low friction and long service life
- Separable and interchangeable components

Dimension series

3GC



Dimensions		
d	536.575 mm	Bore diameter
D	820 mm	Outside diameter
T	152 mm	Total width
d ₁	≈ 664.4 mm	Shoulder diameter of inner ring
B	146 mm	Width of inner ring
C	112 mm	Width of outer ring
r _{1,2}	min. 6 mm	Chamfer dimension of inner ring
r _{3,4}	min. 5 mm	Chamfer dimension of outer ring
a	161 mm	Distance side face to pressure point



Abutment dimensions

d_a	max. 595 mm	Diameter of shaft abutment
d_b	min. 563 mm	Diameter of shaft abutment
D_a	min. 724 mm	Diameter of housing abutment
D_a	max. 788 mm	Diameter of housing abutment
D_b	min. 777 mm	Diameter of housing abutment
C_a	min. 21 mm	Minimum width of space required in housing on large side face
C_b	min. 40 mm	Minimum width of space required in housing on small side face
r_a	max. 5.6 mm	Radius of shaft fillet
r_b	max. 4.6 mm	Radius of housing fillet

Calculation data

Basic dynamic load rating	C	3 910 kN
Basic static load rating	C_0	7 800 kN
Fatigue load limit	P_u	540 kN
Reference speed		450 r/min
Limiting speed		670 r/min
Limiting value	e	0.43
Calculation factor	Y	1.4
Calculation factor	Y_0	0.8

Tolerances and clearances

GENERAL BEARING SPECIFICATIONS

- Tolerances:

bearings: Normal and CL7C, CLN

inch bearings: Normal and CL, deviating width

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

AGA BEARINGS