

## 241/1120-2CS6K30/C3HGEA8



Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. They can be used in a modular system, including housings, sleeves and nuts.

- Accommodate misalignment
- High load carrying capacity
- Low friction and long service life
- Extensive range available sealed for increased reliability
- Increased wear resistance

Bore type

Tapered 1:30

### Dimensions

|                   |                |                                                |
|-------------------|----------------|------------------------------------------------|
| d                 | 1 120 mm       | Bore diameter                                  |
| t <sub>Δdmp</sub> | 0.0 – 0.125 mm | Deviation limits of mid-range bore diameter    |
| t <sub>ΔSL</sub>  | 0.0 – 0.115 mm | Deviation limits of tapered slope              |
| D                 | 1 750 mm       | Outside diameter                               |
| t <sub>ΔDmp</sub> | -0.2 – 0.0 mm  | Deviation limits of mid-range outside diameter |
| B                 | 630 mm         | Width                                          |
| t <sub>ΔBs</sub>  | -1.25 – 0.0 mm | Deviation limits of ring width                 |
| d <sub>2</sub>    | ≈ 1 238 mm     | Shoulder diameter of inner ring                |
| D <sub>1</sub>    | ≈ 1 615 mm     | Shoulder/recess diameter of outer ring         |
| b                 | 22.3 mm        | Width of lubrication groove                    |
| K                 | 12 mm          | Diameter of lubrication hole                   |
| r <sub>1,2</sub>  | min. 15 mm     | Chamfer dimension                              |
| Normal            |                | ISO tolerance class for dimensions             |

### Abutment dimensions

|       |               |                              |
|-------|---------------|------------------------------|
| $D_a$ | max. 1 692 mm | Diameter of housing abutment |
| $r_a$ | max. 12 mm    | Radius of fillet             |

### Calculation data

|                           |       |              |
|---------------------------|-------|--------------|
| AGA performance class     |       | AGA Explorer |
| Basic dynamic load rating | C     | 34 016 kN    |
| Basic static load rating  | $C_0$ | 68 000 kN    |
| Fatigue load limit        | $P_u$ | 3 550 kN     |
| Limiting speed            |       | 20 r/min     |
| Limiting value            | e     | 0.31         |
| Calculation factor        | $Y_1$ | 2.2          |
| Calculation factor        | $Y_2$ | 3.3          |
| Calculation factor        | $Y_0$ | 2.2          |

### Tolerances of run-out

|                                                            |           |                   |
|------------------------------------------------------------|-----------|-------------------|
| Range of section height at inner ring of assembled bearing | $t_{Kia}$ | 100 $\mu\text{m}$ |
| Range of section height at outer ring of assembled bearing | $t_{Kea}$ | 220 $\mu\text{m}$ |
| ISO tolerance class for geol tolerances                    |           | Normal            |

### Radial internal clearance

|                           |                     |
|---------------------------|---------------------|
| Minimum initial clearance | 1 165 $\mu\text{m}$ |
| Maximum initial clearance | 1 300 $\mu\text{m}$ |

### Tolerances of run-out

## GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5,  
tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

#### BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

AGA BEARINGS