

## 241/950 ECA/W33



Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. The design includes features to facilitate relubrication. The bearings can be used in a modular system, including housings, sleeves and nuts.

- Accommodate misalignment
- High load carrying capacity
- Relubrication features
- Low friction and long service life
- Increased wear resistance

Bore type

Cylindrical

### Dimensions

|                   |                |                                                |
|-------------------|----------------|------------------------------------------------|
| d                 | 950 mm         | Bore diameter                                  |
| t <sub>Δdmp</sub> | -0.1 – 0.0 mm  | Deviation limits of mid-range bore diameter    |
| D                 | 1 500 mm       | Outside diameter                               |
| t <sub>ΔDmp</sub> | -0.16 – 0.0 mm | Deviation limits of mid-range outside diameter |
| B                 | 545 mm         | Width                                          |
| t <sub>ΔBs</sub>  | -1.0 – 0.0 mm  | Deviation limits of ring width                 |
| d <sub>2</sub>    | ≈ 1 061 mm     | Shoulder diameter of inner ring                |
| D <sub>1</sub>    | ≈ 1 333 mm     | Shoulder/recess diameter of outer ring         |
| b                 | 22.3 mm        | Width of lubrication groove                    |
| K                 | 12 mm          | Diameter of lubrication hole                   |
| r <sub>1,2</sub>  | min. 12 mm     | Chamfer dimension                              |
| Normal            |                | ISO tolerance class for dimensions             |

### Abutment dimensions

|       |               |                              |
|-------|---------------|------------------------------|
| $d_a$ | min. 998 mm   | Diameter of shaft abutment   |
| $D_a$ | max. 1 452 mm | Diameter of housing abutment |
| $r_a$ | max. 10 mm    | Radius of fillet             |

## Calculation data

|                           |       |              |
|---------------------------|-------|--------------|
| AGA performance class     |       | AGA Explorer |
| Basic dynamic load rating | C     | 27 943 kN    |
| Basic static load rating  | $C_0$ | 55 000 kN    |
| Fatigue load limit        | $P_u$ | 3 000 kN     |
| Reference speed           |       | 110 r/min    |
| Limiting speed            |       | 160 r/min    |
| Limiting value            | e     | 0.33         |
| Calculation factor        | $Y_1$ | 2            |
| Calculation factor        | $Y_2$ | 3            |
| Calculation factor        | $Y_0$ | 2            |

## Tolerances of run-out

|                                                            |           |             |
|------------------------------------------------------------|-----------|-------------|
| Range of section height at inner ring of assembled bearing | $t_{Kia}$ | 90 $\mu$ m  |
| Range of section height at outer ring of assembled bearing | $t_{Kea}$ | 190 $\mu$ m |
| ISO tolerance class for geoal tolerances                   |           | Normal      |

## Radial internal clearance

|                           |             |
|---------------------------|-------------|
| Minimum initial clearance | 480 $\mu$ m |
| Maximum initial clearance | 710 $\mu$ m |

## Tolerances of run-out

## GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5,  
tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

## BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

AGA BEARINGS