

241/850-2CS5K30/C3HGEA8



Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. They can be used in a modular system, including housings, sleeves and nuts.

- Accommodate misalignment
- High load carrying capacity
- Low friction and long service life
- Extensive range available sealed for increased reliability
- Increased wear resistance

Bore type

Tapered 1:30

Dimensions

d	850 mm	Bore diameter
$t_{\Delta dmp}$	0.0 – 0.1 mm	Deviation limits of mid-range bore diameter
$t_{\Delta SL}$	0.0 – 0.1 mm	Deviation limits of tapered slope
D	1 360 mm	Outside diameter
$t_{\Delta Dmp}$	-0.16 – 0.0 mm	Deviation limits of mid-range outside diameter
B	500 mm	Width
$t_{\Delta Bs}$	-1.0 – 0.0 mm	Deviation limits of ring width
d_2	≈ 950 mm	Shoulder diameter of inner ring
D_1	≈ 1 210 mm	Shoulder/recess diameter of outer ring
b	22.3 mm	Width of lubrication groove
K	12 mm	Diameter of lubrication hole
$r_{1,2}$	min. 12 mm	Chamfer dimension
Normal		ISO tolerance class for dimensions

Abutment dimensions

D_a	max. 1 312 mm	Diameter of housing abutment
r_a	max. 10 mm	Radius of fillet

Calculation data

AGA performance class		AGA Explorer
Basic dynamic load rating	C	23 870 kN
Basic static load rating	C_0	45 000 kN
Fatigue load limit	P_u	2 500 kN
Limiting speed		30 r/min
Limiting value	e	0.33
Calculation factor	Y_1	2
Calculation factor	Y_2	3
Calculation factor	Y_0	2

Tolerances of run-out

Range of section height at inner ring of assembled bearing	t_{Kia}	90 μm
Range of section height at outer ring of assembled bearing	t_{Kea}	190 μm
ISO tolerance class for geol tolerances		Normal

Radial internal clearance

Minimum initial clearance	955 μm
Maximum initial clearance	1 070 μm

Tolerances of run-out

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5,
tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

AGA BEARINGS