

248/800 CAK30MA/W20



Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. They can be used in a modular system, including housings, sleeves and nuts.

- Accommodate misalignment
- High load carrying capacity
- Low friction and long service life
- Extensive range available sealed for increased reliability
- Increased wear resistance

Bore type

Tapered 1:30

Dimensions

d	800 mm	Bore diameter
t _{Δdmp}	0.0 – 0.075 mm	Deviation limits of mid-range bore diameter
t _{ΔSL}	0.0 – 0.1 mm	Deviation limits of tapered slope
D	980 mm	Outside diameter
t _{ΔDmp}	-0.1 – 0.0 mm	Deviation limits of mid-range outside diameter
B	180 mm	Width
t _{ΔBs}	-0.75 – 0.0 mm	Deviation limits of ring width
d ₂	≈ 865 mm	Shoulder diameter of inner ring
D ₁	≈ 921 mm	Shoulder/recess diameter of outer ring
K	12 mm	Diameter of lubrication hole
r _{1,2}	min. 5 mm	Chamfer dimension
	Normal	ISO tolerance class for dimensions

Abutment dimensions

D_a	max. 962 mm	Diameter of housing abutment
r_a	max. 4 mm	Radius of fillet

Calculation data

AGA performance class		AGA Explorer
Basic dynamic load rating	C	4 780 kN
Basic static load rating	C_0	12 900 kN
Fatigue load limit	P_u	830 kN
Reference speed		320 r/min
Limiting speed		560 r/min
Limiting value	e	0.15
Calculation factor	Y_1	4.5
Calculation factor	Y_2	6.7
Calculation factor	Y_0	4.5

Tolerances of run-out

Range of section height at inner ring of assembled bearing	t_{Kia}	80 μ m
Range of section height at outer ring of assembled bearing	t_{Kea}	140 μ m
ISO tolerance class for geoal tolerances		Normal

Radial internal clearance

Minimum initial clearance	570 μ m
Maximum initial clearance	750 μ m

Tolerances of run-out

- Tolerances: Normal, P6, P5,
tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

AGA BEARINGS