

231/750 CA/W33



Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. The design includes features to facilitate relubrication. The bearings can be used in a modular system, including housings, sleeves and nuts.

- Accommodate misalignment
- High load carrying capacity
- Relubrication features
- Low friction and long service life
- Increased wear resistance

Bore type		Cylindrical
Dimensions		
d	750 mm	Bore diameter
t _{Δdmp}	-0.075 – 0.0 mm	Deviation limits of mid-range bore diameter
D	1 220 mm	Outside diameter
t _{ΔDmp}	-0.125 – 0.0 mm	Deviation limits of mid-range outside diameter
B	365 mm	Width
t _{ΔBs}	-0.75 – 0.0 mm	Deviation limits of ring width
d ₂	≈ 900 mm	Shoulder diameter of inner ring
D ₁	≈ 1 080 mm	Shoulder/recess diameter of outer ring
b	22.3 mm	Width of lubrication groove
K	12 mm	Diameter of lubrication hole
r _{1,2}	min. 9.5 mm	Chamfer dimension
Normal		ISO tolerance class for dimensions

Abutment dimensions

d_a	min. 790 mm	Diameter of shaft abutment
D_a	max. 1 180 mm	Diameter of housing abutment
r_a	max. 8 mm	Radius of fillet

Calculation data

AGA performance class		AGA Explorer
Basic dynamic load rating	C	16 518 kN
Basic static load rating	C_0	29 000 kN
Fatigue load limit	P_u	1 700 kN
Reference speed		220 r/min
Limiting speed		430 r/min
Limiting value	e	0.28
Calculation factor	Y_1	2.4
Calculation factor	Y_2	3.6
Calculation factor	Y_0	2.5

Tolerances of run-out

Range of section height at inner ring of assembled bearing	t_{Kia}	80 μ m
Range of section height at outer ring of assembled bearing	t_{Kea}	160 μ m
ISO tolerance class for geoal tolerances		Normal

Radial internal clearance

Minimum initial clearance	390 μ m
Maximum initial clearance	580 μ m

Tolerances of run-out

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5,
tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

AGA BEARINGS