

23224-2CS5/VT143



Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. Under normal operating conditions, sealed bearings are almost maintenance-free, keeping service costs and grease consumption low. The design includes features to facilitate relubrication.

- Accommodate misalignment
- High load carrying capacity
- Sealed for increased reliability, with relubrication features
- Low friction and long service life
- Increased wear resistance

Bore type

Cylindrical



| Dimensions        |                |                                                |
|-------------------|----------------|------------------------------------------------|
| d                 | 120 mm         | Bore diameter                                  |
| t <sub>Δdmp</sub> | -0.02 – 0.0 mm | Deviation limits of mid-range bore diameter    |
| D                 | 215 mm         | Outside diameter                               |
| t <sub>ΔDmp</sub> | -0.03 – 0.0 mm | Deviation limits of mid-range outside diameter |
| B                 | 76 mm          | Width                                          |
| t <sub>ΔBs</sub>  | -0.08 – 0.0 mm | Deviation limits of ring width                 |
| d <sub>2</sub>    | ≈ 137 mm       | Shoulder diameter of inner ring                |
| D <sub>1</sub>    | ≈ 193 mm       | Shoulder/recess diameter of outer ring         |
| b                 | 8.3 mm         | Width of lubrication groove                    |
| K                 | 4.5 mm         | Diameter of lubrication hole                   |
| r <sub>1,2</sub>  | min. 2.1 mm    | Chamfer dimension                              |
| Normal            |                | ISO tolerance class for dimensions             |



### Abutment dimensions

|       |             |                              |
|-------|-------------|------------------------------|
| $d_a$ | min. 132 mm | Diameter of shaft abutment   |
| $d_a$ | max. 137 mm | Diameter of shaft abutment   |
| $D_a$ | max. 203 mm | Diameter of housing abutment |
| $r_a$ | max. 2 mm   | Radius of fillet             |

### Calculation data

|                           |       |              |
|---------------------------|-------|--------------|
| AGA performance class     |       | AGA Explorer |
| Basic dynamic load rating | C     | 734 kN       |
| Basic static load rating  | $C_0$ | 930 kN       |
| Fatigue load limit        | $P_u$ | 93 kN        |
| Limiting speed            |       | 690 r/min    |
| Limiting value            | e     | 0.33         |
| Calculation factor        | $Y_1$ | 2            |
| Calculation factor        | $Y_2$ | 3            |
| Calculation factor        | $Y_0$ | 2            |

### Tolerances of run-out

|                                                            |           |                   |
|------------------------------------------------------------|-----------|-------------------|
| Range of section height at inner ring of assembled bearing | $t_{Kia}$ | 6 $\mu\text{m}$   |
| Maximum run-out of inner ring side face to the bore        | $t_{Sd}$  | 9 $\mu\text{m}$   |
| Range of section height at outer ring of assembled bearing | $t_{Kea}$ | 15 $\mu\text{m}$  |
| Perpendicularity of outer ring outside surface             | $t_{SD}$  | 5.5 $\mu\text{m}$ |
| ISO tolerance class for geoal tolerances                   |           | P5                |

### Radial internal clearance

|                           |        |
|---------------------------|--------|
| Minimum initial clearance | 75 µm  |
| Maximum initial clearance | 120 µm |
| Tolerances of run-out     |        |

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5, tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

AGA BEARINGS