

22324/C4W33VA9B1




Spherical roller bearings can accommodate heavy loads in both directions. They are self-aligning and accommodate misalignment and shaft deflections, with virtually no increase in friction or temperature. This variant is optimized for use in continuous casters in the metals industry. The design includes features to facilitate relubrication. The bearings are developed for very slow rotation speed.

- Accommodate misalignment
- High load carrying capacity
- Low friction and long service life
- Increased wear resistance
- Suitable only for very low speed

Bore type

Cylindrical



Dimensions		
d	120 mm	Bore diameter
t _{Δdmp}	-0.02 – 0.0 mm	Deviation limits of mid-range bore diameter
D	260 mm	Outside diameter
t _{ΔDmp}	-0.035 – 0.0 mm	Deviation limits of mid-range outside diameter
B	86 mm	Width
t _{ΔBs}	-0.08 – 0.0 mm	Deviation limits of ring width
d ₂	≈ 152 mm	Shoulder diameter of inner ring
D ₁	≈ 216 mm	Shoulder/recess diameter of outer ring
b	13.9 mm	Width of lubrication groove
K	7.5 mm	Diameter of lubrication hole
r _{1,2}	min. 3 mm	Chamfer dimension
Normal		ISO tolerance class for dimensions



Abutment dimensions

d_a	min. 134 mm	Diameter of shaft abutment
D_a	max. 246 mm	Diameter of housing abutment
r_a	max. 2.5 mm	Radius of fillet

Calculation data

Basic static load rating	C_0	1 120 kN
Limiting speed		20 r/min
Calculation factor	Y_0	1.8

Tolerances of run-out

Range of section height at inner ring of assembled bearing	t_{Kia}	25 μm
Range of section height at outer ring of assembled bearing	t_{Kea}	60 μm
ISO tolerance class for geol tolerances		Normal

Radial internal clearance

Minimum initial clearance	160 μm
Maximum initial clearance	210 μm

Tolerances of run-out

GENERAL BEARING SPECIFICATIONS

- Tolerances: Normal, P6, P5, tapered bore 1:12, tapered bore 1:30
- Radial internal clearance: cylindrical bore, tapered bore

BEARING INTERFACES

- Seat tolerances for standard conditions
- Tolerances and resultant fit

AGA BEARINGS